



"Bringing Brilliance to Every Print
with Innovative DTF Solutions"

TECHNICAL DATA SHEET

Updated August 2024

METALLIC DTF FOIL

PRODUCT FEATURES

Implementation of Stamping Foil Effects with DTF printer.

- Stamping foil-type finish effect.
- Small designs and letters are available.
- No need to weed or cut.
- Splendid brightness.
- Eye-catching color and pattern.
- Various colors are available.

<p>Performance DTF Film Metallic Golden DTF Foil</p>  <p>Metallic Golden 75µm Single Side Cold Peel</p>	<p>Performance DTF Film Metallic Silver DTF Foil</p>  <p>Metallic Silver 75µm Single Side Cold Peel</p>	<p>Performance DTF Film Metallic Bronze DTF Foil</p>  <p>Metallic Bronze 75µm Single Side Cold Peel</p>	<p>Performance DTF Film Metallic Magenta DTF Foil</p>  <p>Metallic Magenta 75µm Single Side Cold Peel</p>
Golden	Silver	Bronze	Magenta

MATERIAL SPECIFICATION

	Material	PET + Aluminum Foil		Thickness	75µm
--	-----------------	---------------------	--	------------------	------

AVAILABLE SIZE

	300mm x 25m 330mm x 25m 600mm x 25m	300mm x 100m 330mm x 100m 600mm x 100m		A4 / A3 / A3+ 350mm x 400mm 400mm x 500mm
--	---	--	--	---

Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District, Haining, Zhejiang, 314400, China
Mob/Skype/WeChat/WhatsApp: +86-15858322153 | Email: maxdtfmr@163.com | Web: <https://www.dtfilmfr.com/>








"Bringing Brilliance to Every Print
with Innovative DTF Solutions"

TECHNICAL DATA SHEET






Updated August 2024

PRINTING & TRANSFER CONDITIONS

	Ink Type		Temp.		Time		Peel		Ink Loading
	DTF Textile Pigment Ink		135°C		8 Seconds 3-3.5Kg		Cold		60%

We recommend using a brush to wipe off the voids and double press (140C, 8 Sec) to ensure the durability of the laundering.

WASHING CONDITIONS

	Washing		Water Temp.		Tumble Dry		Iron		Bleach
	Wool		Cold		Avoid		Inside Out		Not Allowed

It is recommended to wait at least 24 hours after the heat pressing before the first washing.

STORAGE CONDITIONS	SUITABLE FOR
<ul style="list-style-type: none"> ● Temperature: 10-30°C ● Relative humidity: 35-65% ● Keep out of direct sunlight. 	<ul style="list-style-type: none"> ● 100% cotton or 100% polyester ● Mixtures of polyester/cotton ● Acrylic and similar fabrics ● Not suitable for nylon or coated fabrics